

## ISUZU VISIGO INTERURBAN

Manufactured by Anadolu Isuzu


The one and only "Isuzu Manufacturing Management (IMM)" certified Isuzu factory in Europe.

## VISIGO INTERURBAN

## TECHNICAL SPECIFICATIONS

I LUTINIUAL OF LUITIUATIUNO	
Dimensions (mm)	
Maximum Length	9560
Maximum Width	2454
Maximum Height	3368 (including A/C unit)
Wheelbase	4660
Front Overhang	1890
Rear Overhang	3010
Inner Height	max.: 1950
Weights (kg)	
Gross Vehicle Weight	13.500
Engine	
Model	CUMMINS ISB6.7E6C320B EURO VI
Туре	Commonrail Turbo Diesel Intercoole
Number of cylinders	6
Engine volume	6700
Maximum power (kW (HP) /rpm)	239 kW/2300rpm (320) / 2300)
Maximum torque (Nm/rpm)	1200 / 2300
Transmission	Automated
Model	ZF 6AS1010B0
Tyres	
Suspensions	265/70 R19,5
Front	Air Suspension - 2 Air Bellows
1 10111	Independent Suspension
Rear	Air Suspension - 4 Air Bellows
Kneeling System	S
Brake System	<u> </u>
Front / Rear	Disc / Disc
System	EBS, ESC, ABS, ASR
Service	Full Air Brake System, Dual Circuit,
30.1.00	Electronical actuated
Auxiliary Brake	Turbo Brake and Retarder
Fuel Tank	
Fuel Tank Capacity (lt)	250
Diesel Exhaust Fluid Tank(lt)	19
Luggage Compartment	• •
Luggage Capacity (m3)	5.5m3 w/o lift&lift door
	4m3 w/ lift&lift door
Luggage Compartment Lighting	S
Luggage Compartment Door Warning	S
Electrical System ————————————————————————————————————	
Battery	24V (2x12V) -150 Ah
Starter Engine	24V - 5,0 kW
Passenger Capacity*	2 0,0 101
account outputty	39 (Seats) + 10 (Standing) + d (S),
(4 seats per 1 wheelchair)	35 + 12 + d (Opt), 37 + 12 + d (Opt)
( Todato per i Wilcotellali)	00 · 12 · a (opt), 07 · 12 · a (opt)







## **FOLIPMENTS**

o - 16 KW)
Conditioner (24400 kcal/h)
ig air actuated outwards openi
g an actuated cuttrat do open.
c, Air Operated, Adjustable
nti-mist Heater
itt-mist neater
(S)
5)
r



